

Think GAIA

For Life and the Earth

SANYO

Full HD Zoom Camera

VCC-HD4600



SANYO, the first choice for Full HD

- Built-in 10x AF megapixel-rated lens (6.3 - 63mm)
- 1080p Full HD, 30 ips Full Framerate with H.264
- 4-megapixel (2288 x 1712) resolution with MJPEG
- Exclusive Xacti HD-Pro Engine and Optimum IP-Pro Engine
- Quad-Stream
- HDMI Output
- Video Analytics
- Local Recording on SD or HDD *
- Digital PTZ and image stabilization
- Bidirectional Audio
- Universal Power Input PoE, 24V AC and 12V DC & PoE

* Use Sanyo-recommended SD card/HDD.

FULL HD
1920 X 1080



VCC-HD4600
Quad-Stream
Day/Night AF-Zoom
DAY NIGHT

Technical Specifications

Camera

Model No.	VCC-HD4600	
Image sensor	1/2.5" Progressive Scan CMOS	
Number of pixels	Effective 16:9 1920 (H) x 1080 (V) 4:3 2288(H) x 1712(V)	
Minimum illumination (approx.)	Color 2.0lux (F1.8, GAIN HIGH), B/W 0.1lux (F1.8, GAIN HIGH)	
Video S/N ratio	More than 50 dB (AGC off)	
Lens	10x Optical Zoom, 16x Digital Zoom f=6.3 to 63mm, F1.8 to 2.5	
View angle	Horizontal	(16:9) 5.5 - 50.6° (4:3) 5.2 - 48.7°
	Vertical	(16:9) 3.1 - 29.3° (4:3) 3.9 - 37°
	Diagonal	(16:9) 6.2 - 57° (4:3) 6.5 - 58.8°
Auto Focus	Auto/Manual/One-Push	
Backlight compensation	Multi/Center/Face/Off, Mask settings possible	
White balance	ATW/AWC/MWB/Outdoor/Indoor/Fluorescent Adjustable R and B signals in MWB mode	
AGC	Normal/Middle/High/Off Adjustable, gain control in Off mode	
Electronic shutter	1/30, 1/60, 1/100, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/10000 Long shutter : x1, x2, x4, x8, x16, x32	
Electronic iris	On/Off	
Gamma	0.45/1/Mode1/Mode2	
Aperture compensation	On/Off	
Day/Night	True Day/Night	
DNR	3D	
Title	16 Characters	
Motion detection	Yes, Video analytics	
Face detection	Yes	
Privacy mask	On/Off	
Image Stabilizer	Yes	

Network

Image compression	MJPEG / H.264	
Resolution	H.264	<16:9> 1920x1080 / 1280x720 / 640x360 / 320x180 <4:3> 1600x1200 / 1280x960 / 1024 x 768 / 640x480 / 320x240
	MJPEG	<16:9> 1920x1080 / 1280x720 / 1024x576 / 640x360 <4:3> 2288x1712 / 1600x1200 / 1280x960 / 1024x768 / 800x600 / 640x480 / 320x240
Picture quality	Quality: (BASIC, NORMAL, ENHANCED, FINE, SUPER FINE) Bitrate: Chageable	
Frame rate	Max. 30 ips (1920x1080)	
Streaming number	4	
Video streaming	Multi stream H.264 and MJPEG (Max.1920x1080 30 ips)	
Audio compression method	G.711, Bidirectional (Full duplex)	
Protocol	TCP/IP, UDP, HTTP, HTTPS, SMTP, NTP, DHCP, FTP, DDNS, RTP, RTSP	
Simultaneous access capacity	Max. 20	
Security	BASIC authentication (ID/password), SSL supported (Only JPEG), IP filtering	

Interface


Video output	Composite outfor adjustment only), HDMI (mini type)	
SD memory card slot	1(SDHC)	
Network port	10BASE-T/100BASE-TX (RJ45 connector)	
Alarm input/output	2/2	
Audio input/output	Mic in/Line out(3.5Φ mini jack)	
USB port	For dedicated HDD case only	

General

Environmental conditions	Operating	Temperature: -10 to +50°C (14°F to 122°F) Humidity: within 90% RH
	Storage	Temperature: -20 to +70°C (-4°F to 158°F) Humidity: within 70% RH
Power supply	24V AC ±10%, 60 Hz / 12V DC, PoE (IEEE802.3af)	
Power consumption (approx.)	15w	
Dimensions (approx.) (W x H x D)	62.8 x 64.2 x 114.7mm (2.47 x 2.53 x 4.52 inch)	
Weight (approx.)	420g (14.81 oz)	

*Specifications, design and availability are subject to change without notice.

Dimensions



Caution: Please consult the instruction manual to ensure safe and proper operation of the product.



Digital System Company of SANYO Electric Co., Ltd. obtained Quality Management System ISO9001 and Environmental Management System ISO14001 certifications.

Distributed by:



SANYO Electric Co., Ltd.
Digital System Company
<http://www.sanyosecurity.com>